

## SPECIFICATIONS

### FIRE PUMP TEST CONNECTION

Cast brass angle inlet body, size of inlet and number of outlets as selected by model number. Brass NRS hose gate valves with loose bonnets, 3" female N.P.T. inlet x 2-1/2" male hose thread outlet, 2-1/2" male hose thread outlet, 2-1/2" caps and chains. 18" long polished brass cover sleeve and brass identification plate lettered "Pump Test Connection."

### VARIATIONS

-1 - Ductile Iron Body with red glossy polyester coating. Inlet size, location and number of outlets as selected by model number and as indicated on Variation Chart.

-5 - Square Four-way Brass or Ductile Iron Angle Inlet body.

-6 - Male 2-1/2" Hose thread snoots with cap and chain instead of affixed valves. Number of outlets as selected by model number and as indicated on Variation Chart.

-7 - Male 2-1/2" hose thread snoots with cap and chain, swivel inlet hose gate valve with male hose thread outlet. Number of outlets as selected by model number and as indicated on Variation Chart.

## MODEL SELECTION

- 5866
- 5867
- 5868
- 5869

## VARIATION SELECTION

### BODY MATERIAL:

- 1 Ductile Iron

### BODY INLET:

- 5 Sq. Angle, Brass or Ductile

### OUTLETS:

- 6 Male Snoots, Caps, and Chains
- 7 Male Snoots, Caps, and Chains and Removable Swivel Hose Gate Valves



## PRODUCT OPTIONS

### FINISHES: (Brass Body)

- B Rough Brass body with polished brass trim.
- C Rough Chrome body, polished chrome plated trim.

### FINISHES: (Ductile Body)

- B Red glossy polyester coated body, polished brass trim.
- C Red glossy polyester coated body, polished chrome plated trim.

### THREADS:

- N.S.T.
- Other \_\_\_\_\_

Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacturer's tolerance and may change without notice. Potter Roemer - Fire Pro assumes no responsibility for use of void or superseded data. © Copyright Potter Roemer - Fire Pro, Member of Morris Group International™ Please visit [potterroemer.com](http://potterroemer.com) for most current specifications.

**5866-5869 SERIES** Date: 03/27/14

**MEMBERSHIP**



FIRE EQUIPMENT  
MANUFACTURERS'  
ASSOCIATION

**ONFSA**  
NATIONAL IRRE SPINELLER ASSOCIATION, INC.



**CASPE**  
American Society of  
Plumbing Engineers



## POTTER ROEMER/FIRE PRO

Headquarters:  
P.O. Box 3527  
City of Industry, CA  
91744 U.S.A.  
Los Angeles Area  
800-366-3473  
626-855-4890

Also in:  
New York (800) 526-4592  
Chicago (800) 547-3473  
Atlanta (800) 762-0542  
Miami (866) 961-3473  
Dallas (866) 644-3473

[www.potterroemer.com](http://www.potterroemer.com)

**MODEL DIMENSIONS**

Model No.	Size	Type	Overall Height	Radius of Body Swing
5866	4 x 2-1/2	2 Way	28"	6-1/2"



Model No.	Size	Type	Overall Height	Radius of Body Swing
5867	6 x 2-1/2	3 Way	28"	9-3/4"



Model No.	Size	Type	Overall Height	Radius of Body Swing
5868	6 x 2-1/2	4 Way	29"	14-1/2"



Model No.	Size	Type	Overall Height	Radius of Body Swing
5869	8 x 2-1/2	6 Way	29"	21-1/2"



**VARIATION CHART**

Suffix No.	Model No.			
	5866	5867	5868	5869
-1 Ductile Iron Body	No	No	Yes	No
-5 Square Four-way Body, Brass or Ductile Iron	No	No	Yes	No
-6 Male Snoots, Caps and Chains	Yes	Yes	Yes	Yes
-7 Male Snoots, Caps and Chains and Removable Swivel Hose Gate Valves	Yes	Yes	Yes	Yes

Call Potter Roemer - Fire Pro for current listings and approvals. Dimensions are subject to manufacturer's tolerance and may change without notice. Potter Roemer-Fire Pro assumes no responsibility for use of void or superseded data. © Copyright Potter Roemer- Fire Pro, Member of Morris Group International™ Please visit [potterroemer.com](http://potterroemer.com) for most current specifications.

**5866-5869 SERIES** Date: 03/27/14

**MEMBERSHIP**



**POTTER ROEMER/FIRE PRO**

Headquarters:  
P.O. Box 3527  
City of Industry, CA  
91744 U.S.A.  
Los Angeles Area  
800-366-3473  
626-855-4890

Also in:  
New York (800) 526-4592  
Chicago (800) 547-3473  
Atlanta (800) 762-0542  
Miami (866) 961-3473  
Dallas (866) 644-3473

[www.potterroemer.com](http://www.potterroemer.com)